

AXPOLY® ABS52 1007

Product information sheet: Black ABS resin grade

Description: This 100% recycled polymer is a high quality injection moulding compound suitable for complex technical shapes and load bearing parts with good surface finish. Example applications are engineering components in construction products and durable vehicle parts.

Export tariff code: 3903300000

Product physical properties

Product grade: Axpoly® ABS52 1007

| Test parameter | Method | Unit | Value |
|---------------------------------------|----------|----------|-------|
| Physical properties | | | |
| Density | ISO 1183 | g/cm³ | 1.075 |
| Rheological properties | | | |
| Melt Flow (10 kg @ 220°C) | ISO 1133 | g/10mins | 22 |
| Mechanical properties | | | |
| Tensile strength (@ 23°C) | ISO 527 | МРа | 37 |
| Flexural Modulus (@ 23°C) | ISO 178 | MPa | 2750 |
| Notched Izod Impact strength (@ 23°C) | ISO 180 | kJ/m² | 5.0 |

Please note this polymer is not approved for use in food, medical or toy applications. All grades are tested to ISO standards, and certified as ROHS and REACH compliant.

All Axpoly polymers are tested and have proven to be well below the permitted POPs levels of 500ppm for articles and mixtures, and do not contain phthalates.





The data is provided as a guide only and does not create any liability, warranty or guarantee of performance. The values may vary from the above information and do not indicate specific limits. This document does not create any liability, warranty or guarantee of product performance. It is the buyer's responsibility to determine the suitability of the material for the end application.

www.axiongroup.co.uk/AxpolyABS

AXION POLYMERS IS PART OF

S. Norton

Responsible Recycling