

## AXPOLY® PS52 1044

### Product information sheet: Black PS resin grade

**Description:** Polystyrene-rich injection moulding compound, made with 100% recycled polymer.

### Product physical properties

Product grade: Axpoly® PS52 1044

Test parameter	Method	Unit	Value
Physical properties			
Density	ISO 1183	g/cm <sup>3</sup>	1.06
Rheological properties			
Melt Flow (10 kg @ 220°C)	ISO 1133	g/10mins	9
Mechanical properties			
Tensile strength (@ 23°C)	ISO 527	MPa	30
Flexural Modulus (@ 23°C)	ISO 178	MPa	2600

**Please note** this polymer is not approved for use in food, medical or toy applications. All grades are tested to ISO standards, and certified as ROHS and REACH compliant.

All polymers are tested and have proven to be well below the permitted POPs levels of 500ppm for articles and mixtures, and do not contain phthalates.



The data is provided as a guide only and does not create any liability, warranty or guarantee of performance. The values may vary from the above information and do not indicate specific limits. This document does not create any liability, warranty or guarantee of product performance. It is the buyer's responsibility to determine the suitability of the material for the end application.

<https://axiongroup.co.uk/products/recycled-plastics/>

Indigo Street, Off Langley Road South, Salford. M6 6RX  
Tel. +44 161 737 6124  
E. [info@axionpolymers.com](mailto:info@axionpolymers.com)

AXION POLYMERS IS PART OF

